

Manual callpoint, flying leads, 470 Ohm series resistor

DM700R

The DM700R is a red manual call point using flying leads between the head of the MCP and the base. It has a built in 470 Ohm series resistor.

Specifications

Material - standard	Self-extinguishing Noryl SE 100
Max. contact rate resistive load	
50 VAV or 30 VDC	8.0 A
50 VDC	3.0 A
Contact resistance (max)	50 mohms
Standard colour	Red - RAL N° 3020
Ambient temperature range	-40 °C to +85 °C
Maximum relative humidity	90% RV
IP Rating	IP24D

Ordering Information

DM700R	Manual callpoint, flying leads, 470 Ohm series resistor
DM711	Break glass, EN54, Aritech logo
DM782	Hinged transparent MCP protection cover
DM715	EN54 universal glass for manual call point
DM784	Call Point Test Key
DM788	Surface mount box without connectors, red
DM790	Flush mount cradle with connectors
DM795	Flush mount cradle, connectors & forkgrrips
DM798	Breakable seal for MCP
DM800	Resettable element for MCP DM700/KAL450



- Easy to install
- With or without series resistor
- May be used with breakglass or be resettable
- Easy to replace glass
- Surface and flush mounting options
- High quality micro switch
- Complies with BS5839 p. 2
- Operates after long period of disuse
- Standard fire symbol
- Preformed mounting slots
- Standard accepts hinged cover
- Key test facility
- Named glass (option)