

## Fliptop Housing 230mm & Wall Bracket IP66

# CHF230

Gain easy access to your outdoor security cameras with GE-Security innovative fliptop-style housing. The CHF230 model accommodates a camera and lens of 230 mm. Die-cast aluminium gives the CHF230 housing strength and durability while keeping each unit lightweight. Without the blower, both housings have weatherproof ratings of IP66. A plate located at the back of the housing allows you to route one or two cables through individual outlets, avoiding damage to cables while keeping the inside of the housing dry. The heavy-duty aluminium sunshield protects the camera from too much light. For environments where weather conditions demand heating or cooling, the CHF230 has an optional heater or blower unit available. Optional mounting brackets are available for the CHF230 housing. Position a camera on a wall or ceiling, in a corner, or on a pole.

### Specifications

Dimensions	230 x 76 x 76 mm
Power	31 W
Operating temperature	-20 to +50°C
Material	Die-cast aluminium
Colour	White RAL9002
Window	65 x 65 mm
IP rating	IP66

### Ordering Information

CHF230	Fliptop Housing 230mm & Wall Bracket IP66
CHF270	Fliptop Housing 270mm & Wall Bracket IP66
CHOF230	Fliptop Housing 230mm IP66 & Cable Management Wall Bracket
CHOF270	Fliptop Housing 270mm IP66 & Cable Management Wall Bracket
CBR+H6	Ceiling mount bracket for FlipTop Housings



- Die-cast aluminum construction
- Weatherproof with an IP66 rating
- Flips open for easy access to the security camera
- Optional heater/blower kit available
- Interchangeable cable access
- Multiple mounting options available