



LV-17W

17" TFT Flatscreen CCTV monitor

New attractive silver finish of the LV-17W is the next generation professional LCD monitor from GE-Security. A new hi-resolution, low lag panel is the heart of this high end display.

New features include Picture and Picture from two different sources, so a single monitor can display two different display sources (VGA and Video) at the same time, plus an over/under scan option.

The high contrast and brightness LV-17W color 17" LCD monitor is ideally suited to a wide range of applications, including most retail, industrial and commercial environments. Light in weight, compact and with a low current requirements, the LCD monitor represents the future in surveillance requirements.

An array of different compatible wall mounts and desk brackets are also available (contact your sales office for info)



Standard Features

- **New slimline silver design**
- **Latest generation High Contrast, Brightness, low lag TFT panel**
- **Industry standard BNC, S-video, Audio Loop Through**
- **Picture and Picture function**
- **High viewing angle**
- **Under/Over scan function**
- **NTSC/PAL auto recognition**



LV-17W

17" TFT Flatscreen CCTV monitor

Specifications

| | |
|--------------------------------|--|
| LCD Display | 17" TFT |
| Resolution | 1280 x 1024 SXGA |
| Effective Display area | 337.92 x 270.34 mm |
| Pixel Pitch | 0.264 x 0.264 mm |
| Colour | 16.7 M |
| Response Time | 15/10 ms |
| Contrast Ratio | 500 : 1 |
| Brightness | 250 cd /m ² |
| Viewing Angle | 170 (H) x 170 (V) |
| Input Signal | Video (loop-thru) , S-Video (Loop-thru) and VGA |
| VGA Signal | Analogue VGA / 15 Pin-D-Sub connector |
| Scan Frequencies | Horizontal: 30 K ~ 80 KHz Vertical: 56 ~ 75Hz |
| Video input | 1.0 Vp-p 75 / BNC in/out, Y/C input, PAL: 15.625 KHz |
| Front panel controls | Power, Auto Tuning, Menu, Volume, Brightness, Contrast |
| OSD controls | Brightness, Contrast, Auto adjust, PIP, Phase Clock, H. Position, V. Position, Sharpness,etc |
| Supply voltage | 12 Vdc, 3 Amp (power supply included) |
| Power consumption (max) | 50W (max) |
| Operating temperature | 0°C to + 40°C |
| Operating humidity | 10% to 85% |
| Dimensions | 375(W) x 370(H) x 170(D) mm |
| Net weight | 5kg |
| Safety & EMI | FCC, CE, UL, CUL, BSMI |
| Audio | 1x Phono (loop-thru) 1 Watt max |

Ordering Information

| Part No. | Description |
|----------|---------------------------------|
| LV-15W | 17" TFT Flatscreen CCTV monitor |
| LV-17W | 17" TFT Flatscreen CCTV monitor |
| LV-19W | 19" TFT Flatscreen CCTV monitor |



GE Security

www.gesecurity.com

As a company of innovation, GE Security reserves the right to change product specifications without notice. For the latest product specifications, visit GE Security online or contact your GE Security sales representative.

IPS-LV-17W-2004-10-11 10:26:56 Released : 15.09.2004;