

Fliptop Housing 270mm IP66 & Cable Management

CHOF270

FipTop housing with cable managed wall bracket

Gain easy access to your outdoor security cameras with GE-Security innovative fliptop-style housing. The CHOF270 model accommodates a camera and lens of 270 mm. Die-cast aluminum gives the CHOF270 housing strength and durability while keeping each unit lightweight. Without the blower, both housings have weatherproof ratings of IP66. A plate located at the back of the housing allows you to route one or two cables through individual outlets. Avoid damage to cables while keeping the inside of the housing dry. The heavy-duty aluminum sunshield protects the camera from too much light. For environments where weather conditions demand heating or cooling, the CHOF270 has optional a heater, blower unit available. Optional mounting brackets are available for the CHOF270 housing. Position a camera on a wall, in a corner, or on a pole.

Specifications

Dimensions	270 x 76 x 76 mm
Power	31 W
Operating temperature	-20 to +50°C
Material	Die-cast aluminium
Colour	White RAL9002
Window	65 x 65 mm
IP rating	IP66

Ordering Information

CHOF270	Fliptop Housing 270mm IP66 & Cable Management Wall Bracket
CHOF230	Fliptop Housing 230mm IP66 & Cable Management Wall Bracket
CHF230	Fliptop Housing 230mm & Wall Bracket IP66
CHF270	Fliptop Housing 270mm & Wall Bracket IP66
CBR+H6	Ceiling mount bracket for FlipTop Housings



- Die-cast aluminum construction
- Weatherproof with an IP66 rating
- Flips open for easy access to the security camera
- Optional heater/blower kit available
- Interchangeable cable access
- Multiple mounting options available
- Cable managed wall bracket