

KTD-440N

Monitor Expansion Chassis - Expands System by 32 Monitor Output

The KTD-440N Monitor Expansion Chassis provides the Digiplex IV system with 32 additional monitor outputs. The KTD-440N can hold up to two video input cards. The first switches inputs for monitors 33 through 48, the second switches inputs for monitors 49 to 64. The KTD-440N can also accept up to eight video output cards and one CPU card. Each monitor expansion chassis is supplied with one KTD-446 Power Supply.

**Standard Features**

KTD-440N

Monitor Expansion Chassis - Expands System by 32 Monitor Output

Specifications

Electrical Input	
Voltage	100 - 240 VAC @ 50/60 Hz
Power	25 V
Data signal	RS422
Computer interface	RS232
Output	
Remote data signal	RS422
Connections	
Computer interface	RJ45
PC keyboard	6-pin mini DIN
Power	Molex Mini-fit, Jr., 5557 dual-row, 2-pin
Video expansion bus	3M mini D-sub, 68-pin
Environmental	
Operating temperature	0 °C to +70 °C
Mechanical	
Dimensions (H x W x D)	13.34 (3 U) x 48.26 x 28.6 cm
Weight	6 kg
Material	Die-cast steel
Finish	Custom gray paint

Ordering Information

Part No.	Description
KTD-440N	Monitor Expansion Chassis - Expands System by 32 Monitor Output



GE Security

www.gesecurity.com

As a company of innovation, GE Security reserves the right to change product specifications without notice. For the latest product specifications, visit GE Security online or contact your GE Security sales representative.

IPS-KTD-440N-2004-10-11 15:52:18 Released : 27.05.2004;