

KTD-441-1

Slave Chassis, Additional 64 Video Inputs per Chassis (previously KT)

The KTD-441-1 Slave Chassis provides the Digiplex IV system with 64 additional video inputs. Seven of these units expand the system to its maximum capacity of 512 video inputs. A ribbon cable connects the slave chassis to the master switcher chassis via the gathering panel. It features LEDs for monitoring and system diagnosis. The KTD-441-1 Slave Chassis can hold up to two video input cards. The first switches inputs for monitors 1 through 16, the second switches inputs for monitors 17 through 32. Each slave chassis comes supplied with one KTD-446 power supply.



Standard Features



KTD-441-1

Slave Chassis, Additional 64 Video Inputs per Chassis (previously KT)

Specifications

Electrical	
Input	
Voltage	100 - 240 VAC @ 50/60 Hz
Power	5 V
Connections	
Power	Molex Mini-fit, Jr., 5557 dual-row, 2-pin
Video	BNC connectors
Video output bus	3M mini D-sub, 36-pin
Video expansion bus	3M mini D-sub, 68-pin
Environmental	
Operating temperature	0 °C to +70 °C
Mechanical	
Dimensions (H x W x D)	8.9 (2 U) x 48.26 x 28.6 cm
Weight	6 kg
Material	Die-cast steel
Finish	Custom gray paint

Ordering Information

Part No.	Description
KTD-441-1	Slave Chassis, Additional 64 Video Inputs per Chassis (previously KT)



GE Security

www.gesecurity.com

As a company of innovation, GE Security reserves the right to change product specifications without notice. For the latest product specifications, visit GE Security online or contact your GE Security sales representative.

IPS-KTD-441-1-2004-10-11 15:52:50 Released : 27.05.2004;