

**Sounder, 32 tones - high output RED****AS269HO**

The AS260 series feature a wide range of sounders and sounder / beacons tailored for every application: stand-alone or in combination with fire detectors. The AS260HO is a red coloured, high output sounder with 32 selectable tones.

**Specifications**

Operation	2 h Continuous
Supply voltage	9 - 28 VDC
Current consumption	
(see tone table in manual)	240 mA $\pm$ 20 mA
Starting current	
Sound output @ 1 metre	Up to 120 dB(A)
Number of tones	32
Frequency stability	$\pm$ 0.15 %
Automatic synchronisation	Synchronised Start
Line monitoring input	Polarised input
Housing	ABS plastic
Lens	
Ingress protection	IP42
Operating temperature	-25°C to +55°C
Dimensions in mm ( $\emptyset$ x D)	
Weight	0.58 kg

**Ordering Information**

AS269HO      Sounder, 32 tones - high output RED



- Low current consumption
- High sound output
- Multiple tones selection on most models
- 9-24 VDC and 230 VAC models
- Automatic synchronisation
- Suitable for multiple stage evacuation
- Red and white colour body
- IP65, intrinsic safe and high output versions
- Low profile and deep base versions
- Beacons with intelligent xenon flash
- A choice of red, clear or blue lenses for beacons