

ATS1110

16 Area Keypad, 2x16 char. LCD keypad

The ATS1110

The ATS1110 is a modern ergonomic design and has a clearly readable text on a 2 x 16 characters LCD for displaying system programming, alarm and access control functions. The viewing angle of the display is adjustable via the keypad as well as the volume level of the built-in buzzer. Four arrow keys will navigate the user easily through the programming and operational features and 6 additional function keys will complete this user-friendly interface. Four status LEDs will continuously update the user on mains condition, faults, access control and alarms. The Arming Station can display the status of 16 areas using 16 LEDs on the front, while the LCD shows details of alarms or a pre-programmed text.

The ATS1110 can be mounted at a distance of 1.5 km from an Advisor MASTER panel. The backlit screen and keys highlight the keypad for day and night use, even in places where lighting is poor the display has an excellent performance. The backlit functionality is programmable. In non-alarm situation the keypad can scroll a free programmable text. A LED flashes when an area is in alarm, is off when an area is disarmed and is constantly lit when an area is armed. The ATS1110 features one open collector output for door control and one dedicated request to exit input.



Standard Features

- **2 x 16 characters LCD**
- **user adjustable buzzer**
- **user adjustable LCD contrast**
- **16 Area indication**
- **door release indication**

ATS1110

16 Area Keypad, 2x16 char. LCD keypad

Specifications

| | |
|-----------------------------|------------------------|
| Supply voltage | 9-14 VDC Max |
| Current consumption | |
| Normal (all areas armed) | 26 mA @ 13.8 VDC |
| Maximum | 95 mA @ 13.8 VDC |
| Outputs | |
| Open collector | 15 VDC Max @ 50 mA Max |
| Dimensions | |
| with cover (W x H x D) | 92 x 165 x 25,4 mm |
| Operating teperature | 0 to +50°C |
| Humidity | 95% non condensing |

Ordering Information

| Part No. | Description |
|----------|--|
| ATS1110 | 16 Area Keypad, 2x16 char. LCD keypad |
| ATS1111 | 16 Area Keypad, 4x16 char. LCD keypad |
| ATS1115 | 16 Area Keypad, 2x16 char. LCD keypad, with build-in card reader |
| ATS1116 | 16 Area Keypad, 4x16 char. LCD keypad, with build-in card reader |



GE Security

www.gesecurity.com

As a company of innovation, GE Security reserves the right to change product specifications without notice. For the latest product specifications, visit GE Security online or contact your GE Security sales representative.

IPS-ATS1110-2004-10-11 08:38:09 Released : 26.03.2004;