

KTD-442

Expansion Chassis - Accepts Inputs from KTD-440 for Monitors 33-64

The KTD-442 Expansion Chassis accepts video inputs from up to four slave chassis for output on monitors 33 to 64. These inputs are transmitted to the gathering panel, which manages video signals going into the master switcher chassis. The gathering panel can accommodate two KTD-442 Expansion Chassis, each of which can accommodate four slave chassis. Each expansion chassis comes equipped with one KTD-446 power supply. For a detailed view of the expansion scheme, see the system layout diagrams in the product specification insert.

**Standard Features**

KTD-442

Expansion Chassis - Accepts Inputs from KTD-440 for Monitors 33-64

Specifications

Electrical Input	
Voltage	100 - 240 VAC @ 50/60 Hz
Power	18 V
Connections	
Power	Molex Mini-fit, Jr., 5557 dual-row, 2-pin
Video output bus	(4) 3M mini D-sub, 36-pin
Video expansion bus	(4) 3M mini D-sub, 68-pin
Environmental	
Operating temperature	0 °C to +70 °C
Mechanical	
Dimensions (W x H x D)	13.34 (3 U) x 48.26 x 28.6 cm
Weight	5.9 kg
Material	Steel and die-cast aluminium
Finish	Custom gray paint

Ordering Information

Part No.	Description
KTD-442	Expansion Chassis - Accepts Inputs from KTD-440 for Monitors 33-64



GE Security

www.gesecurity.com

As a company of innovation, GE Security reserves the right to change product specifications without notice. For the latest product specifications, visit GE Security online or contact your GE Security sales representative.

IPS-KTD-442-2004-10-11 15:53:09 Released : 27.05.2004;